

## TRIODES

TITLE	CATH	Vh	Ih (A)	Max. Va	Ia m/a	Ia peak m/a	Max. Wa	G.m.	$\mu$	Ra	MAX Mc/s	BASE	DESCRIPTION	PIN CONNECTIONS											
														1	2	3	4	5	6	7	8	9	TC		
1720	DH	1.5	0.083	100				0.7					Spec.		G	F	F	A							
1721	DH	1.5	0.083	100				0.8					Spec.		G	F	F	A							
1728	IH	10.0	0.32	140					15				USM4												
1732	IH	4.0	1.0	250			5	3.75	12	2860			B5		A	G	H	H	C						
1734	DH	20.0	62.0	12000			15000		22	3500	22		Nil	Double-ended, water cooled											
1735		35.0	0.1	200				3.75	10	2650			B5	Low impedance											
1750	IH	6.3	0.8	300	50		5	3.0	18	6000			0	Double Triode	-	H	-	G	G'	-	H	C		A/A	
1754	DH	5.0	3.9	2000			35		39				Spec.	Transmitter											
1755	IH	12.6	0.25	250	25		5		5				0	Transmitter	-	H	A	-	G	-	H	C			
1759	IH	6.3	1.1	3500			10	2.2	16				0		-	H	-	-	-	-	H	C		A/G	
1763	IH	6.3	0.4	150			2.25	1.1	55	5000	500		B7G	Miniature	G	C	H	H	G	C	A				
1769	IH	2.5	0.8	275	1.025			1.225	100	32000			6Pin	Double diode triode (high $\mu$ )	H	A	A'	A''	C	H				G	
1770	IH	6.3	0.3	300			2.5	2.6	20	7700			B8G		H	A	-	-	INT	G	C	H			
1774	DH	5.0	0.25	180				1.8	8.5	4700			BC4		F	A	G	F							
1778	DH	4.2	1.0	200			2	1.0	6	6000			BC4		F	A	G	F							
1779	DH	2.1	1.0	130	0.8			0.51	29.6	58000			4pin		F	A	G	F							
1780														Transmitting Twin Triode.											
1782	DH	20.0	72.0	18000	1300		25000	6.82	40	5860			Spec.	Water cooled											
1797	DH	20.0	59.0	17500			20000	5.5	33	6000	5		Nil	Water cooled											
1817	DH	1.4	0.05	110	2.3			0.8	8.8	10700			0		-	F	A	-	G	-	F	-			
1818	DH	1.4	0.05	120	C.2			0.31	65				0	Diode, High $\mu$ Triode	-	F	A	-	A'	-	F	-		G	
1819	IH	6.3	0.3	275	5.2			1.45	14	9625			0	Detector Amplifier	-	H	A	-	G	-	H	C			
1820	DH	1.4	0.05	110	0.15			0.275	65	0.24			0	Diode Triode	S	F	A	-	A'	-	F	-		G	
1831	DH	2.5	2.5	300	60		15	5.2	4.2	800			M4		F	A	G	F							
1867	IH	6.3	0.8	300	125		5.5	3.2	35	11000			M7	Double Triode	H	A	G	C	G'	A'	H				
1885	IH	6.3	0.8	300				2.4	58	24000			M6	Double Triode	H	A	A'	G	C	H					
1887	IH	6.3	0.3	250	0.9			1.1	100	91000			0	Double Diode Triode	-	H	A	A'	A''	-	H	C		G	
1896	IH	6.3	0.3	250			1	1.6	36	22500			0	Double Triode	-	H	A	C	G'	A'	H	C		G	
1909	IH	6.3	0.3	300				1.5	100	86000			0	Metal Valve	Sh	H	-	A	-	-	-	H	C		G